

# 6822

## Mobile Full Page Printer



- Choice of portable or fixed-mount configurations
- Wireless printing via optional Bluetooth holder for portable and fixed-mount configurations
- Easy loading of up to 3-ply paper from internal or external paper trays
- 512k flash memory can store DBCS fonts such as Korean and Chinese
- Optional HHC holders and docks for Intermec CN3/e, CN4/e and CN70/e Series mobile computers
- Fast two-page-per-minute print time helps get the work done fast

The Intermec® 6822 printer produces high-quality customer invoices, receipts, load reports, transfers and other documents for route accounting applications. The real time accounting structure provided by the 6822 printer and Intermec handheld computers facilitates route delivery settlement and ensures customer information is always current.

Customers have the choice of portable or fixed-mount configurations depending on mobility requirements.

### Portable

The Intermec 6822 printer provides flexibility and mobility. It features a handle for easy carrying and a compact tray which

holds enough paper for an entire day. A seat-mount strap is available to secure the printer in vehicles with bench seats. An optional, soft-sided carrying case provides a sealed compartment inside the case cover for storage of invoices.

### Fixed Mount

The fixed mount model is ideal for applications where mounting the printer in a vehicle is preferred. The mobile computer holder can be mounted either to the side of the printer or remote from the printer, whichever is most convenient. Although the printer is safely mounted to the vehicle, a quick release feature allows one-step removal of the printer for swapping from one vehicle to another.

**Application**

Portable dot matrix receipt printer

**Portable**

Optional AC foot, Intermec CN3/e, CN4/e and CN70/e Series terminal holder top mount.

**Physical Characteristics**

**Length:** 38.1cm (15")

**Width:** 41.9cm (16.5")

**Depth:** 13cm (5.13")

**Weight:** 5.67kg (12.25 lbs.)

**Portable with AC Foot****Physical Characteristics**

**Length:** 38.1cm (15")

**Width:** 48.3cm (19")

**Depth:** 13cm (5.13")

**Weight:** 5.67kg (12.25 lbs.)

**Fixed Mount**

- Base is 32.5cm (12.75") x 35.5cm (14").
- Refer to the 6820 printer user's guide (961-019-013) for specific configurations for the following:
  - Custom with Intermec CN3/e, CN4/e and CN70/e Series terminal holder top mount

**Physical Characteristics**

**Length:** 36.8cm (14.5")

**Width:** 47cm (18.5")

**Depth:** 20.3cm (8")

**Weight:** 6.55kg (14.4 lbs.)

**Environment**

**DC Operating Temperature:** -20° to 60°C (-4° to 140°F)

**AC Operating Temperature:** -20° to 45°C (-4° to 113°F)

**Storage Temperature:** -30° to 70°C (-22° to 158°F)

**Humidity:** 5% - 95% (non-condensing)

**Drop spec:** .6m (2 ft.) drop to concrete (6822P only)

**Power Supply**

**Vehicle:** low amperage draw; protection from voltage irregularities

**Lead Acid Battery:** 12-volt standard cam-corder type. Full charge will print dozens of tickets. Time to recharge is one hour.

**AC Adapter:** 115/230 volt

**Print Specifications**

**Characteristics:** Dot matrix, Bi-directional, Graphics capable

**Print speed:** 2 pages per minute

**Print width (min/max):** 7.5 inch/8.5 inch

**Type styles:** (char/line) Normal 80, Bold 40, Condensed 136, Bold condensed 68

**Media**

1 to 3-ply fan fold, 7.5" to 8.5" x 11", Carbonless, NCR paper with adhesive tacking on left border

**Ribbon**

- One color cartridge, black, 2,250,000 character life
- One color cartridge, purple, 3,750,000 character life

**Regulatory Approvals**

FCC Class B, CE mark

**Options**

- 6820 Developers Kit
- Bluetooth in Mobile Computer holder

**Note**

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

**Accessories**

Universal Power Supply, Installation kits, data cables, Paper Tray, Soft sided carrying case, restraining straps

**Warranty**

One year, additional Medallion service available.

**Safety Approvals**

**North America:** UL and cUL Listed, UL 60950-1

**Europe:** EN 60950-1, e-Marked, EN 55022

**Mexico:** NYCE Certified, NOM 19

**Other Countries:** IEC 60950-1

**EMC Approvals**

**US:** FCC Class B

**Canada:** Industry Canada ICES-003 Class B

**EU/EFTA countries:** EN 55022 Class B, including telecom port and DC conducted emissions

**EU/EFTA countries:** e-mark

**North America**

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348 2600  
Fax: (425) 355 9551

**North Latin America**

Mexico  
Phone: (+52) 55 52 41 48 00  
Toll Free NOLA:  
01800 490 4990

**South Latin America**

Brazil  
Phone: (+55) 11 3711 6770  
Fax: (+55) 11 5502 6780

**Europe, Middle East & Africa**

Reading, United Kingdom  
Phone: (+44) 118 923 0800  
Fax: (+44) 118 923 0801

**Asia Pacific**

Singapore  
Phone: (+65) 6303 2100  
Fax: (+65) 6303 2199

**Media Sales**

EMEA: (+31) 24 372 3167  
USA: (513) 874 5882  
<http://intermec.custhelp.com>

**Sales**

Toll Free NA: (800) 934 3163  
Toll in NA: (425) 348 2726  
Freephone ROW:  
00800 4488 8844

**OEM Sales**

Phone: (425) 348 2762

**Customer Service & Support**

Toll Free NA: (800) 755 5505  
Toll in NA: (425) 356 1799  
EMEA: [intermec.custhelp.com](mailto:intermec.custhelp.com)

**Internet**

[www.intermec.com](http://www.intermec.com)

**Worldwide Locations**

[www.intermec.com/locations](http://www.intermec.com/locations)

